



## ◆ Main Features

- **Max. 240fps @ CIF recording**
- USB 2.0 supported
- 10/100 Base Network
- Max 2 HDD supported
- 1 SPOT supported (BNC)
- VGA supported
- Backup supported during playback
- Multi language supported
- AVI backup supported
- Compatible with MPR series – MPR client function supported

		STA-73
Video IN		16
Video Display		1,4, 9, 16
Monitor Out		1 CH Composite
VGA Out		1CH
Spot Out		1CH
Audio In / Out		4 In / 1 Out
Audio Compression		G.723
Display Resolution		720 X 480(NTSC)
Recording Resolution		720X480, 720X240, 360X240(NTSC)
Video Compression		Mpeg4 Level 1,2,3
Display Frame	NTSC	480Fps
	PAL	400Fps
Rec. Frame	NTSC	CIF 240Fps
	PAL	CIF 200Fps
OS		Embedded Linux
Network		10/100 BaseT (1EA)
USB		USB 2.0 (Front 1EA, Rear 1EA)
SATA		(MAX 2EA HDD + 1 CD-RW)
Console		RS232C
PTZ		RS485
Alarm Function		4 In / 1 Out
Front Key		33 Key
Remote Controller		YES
WatchDog		YES
Front LED		Power, Network, HDD
Demension		359(W) X 390(D) X 70(H)mm

Operation temperature	0 ~ 45□
Operation humidity	5 ~ 85%
Weight	With Out CDRW, HDD (3.5kg)
Power	Adapter 100/240VAC , 60/50Hz , 1.5A